

## WR 2002, digital 2-channel rework station, 250 W (300 W)



The repair professional with 2 channels

One station for all requirements at the repair workplace. Unique compatibility - connection of all tools possible. 2 independent tool channels with automatic tool recognition guarantee simultaneous operation of 2 tools. All tools are permanently ready for use.

The Weller repair station WR 2 is a versatile soldering and desoldering station for professional repair work on electronic assemblies of the latest technology in industrial production engineering as well as in the repair and laboratory sector. The WR 2 has two independent tool-specific channels with automatic tool recognition and activation. Simultaneous soldering and desoldering or soldering and hot air soldering is thus possible at any time. With the exception of the Weller High-Speed Tools, all soldering tools such as soldering irons, solder baths, desoldering irons or hot air irons can be operated at the repair station.

- Small repair set for all repair work
- Simultaneous operation of hot air and desoldering is not possible

Products for the electronic industry



- Overcurrent release: 1.6 A
- IPC compliant: Tip to ground Corresponds to IPC-J-001
- Built-in pump: intermittent operation 30/30 s
- Max vacuum: 0.7 bar
- no USB interface
- Max. Hot air quantity l/min (depending on tool): 10
- WT compatible

<b>item number</b>	<b>WL26272</b>
model	WR 2002
model line	WR 2
manufacturer	WELLER
manufacturer item number	T0053380699N
GPSR manufacturer information	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller.eu
length	237 mm
width	235 mm
height	102 mm
scope of supply	1x WR 2 supply unit 1x WP 65 soldering iron 1x desoldering iron DSX 80 1x safety shelf WDH 10 1x safety rest WDH 30 1x soldering tip LT B, chisel shape 2.4 x 0.8 mm 1x desoldering nozzle DX 113HM, outer/inner Ø 2.5/1.2 mm 1x mains plug 1x operating instructions
length in inches	9.2 in
width in inches	10.75 in
height in inches	4.02 in
order unit	1 piece
content unit	1 piece
power	250 W
nominal power	300 W
voltage	230 V
temperature range °C	50 – 550 °C
temperature range °F	150 – 950 °F

temperature accuracy °F	±17 °F
station type	desoldering station
included stand	WDH10, WDH30
included desoldering tip	DX113HM
included soldering tip	LT-B
included desoldering iron	DSX 80
included soldering iron	WP 80
temperature stability °C	±2 °C
temperature stability °F	±4 °F
number of channels	2
ESD safe	yes

