

WR 2000A, digital 2-channel rework station, 250 W (300 W)



Rework on highest level

One station meets the requirements of a rework workplace. Unique connecting compatibility of all tools. 2 independent tool channels with automatic tool recognition guarantee the simultaneous operation of 2 soldering tools. Tools are permanently ready for use.

The Weller Rework station WR 2 is a versatile soldering and desoldering station for professional repair work on electronic components of the latest technology in industrial production technology as well as in the repair and laboratory sector. The WR 2 has two independent tool-specific channels with automatic tool recognition and activation. Simultaneous soldering and desoldering or soldering and hot air soldering is thus possible at any time. With the exception of the Weller High-Speed Tools, all soldering tools such as soldering irons, solder baths, desoldering irons or hot air irons can be operated with the rework station.

- with built-in vacuum pump

- also connection for soldering iron and hot air operation
- Simultaneous operation of 2 soldering tools
- All soldering tools up to 200 W connectable
- Overcurrent release: 1.6 A
- IPC compliant: Tip to ground Corresponds to IPC-J-001
- Built-in pump: intermittent operation 30/30 s
- Max vacuum: 0.7 bar
- Max. Hot air quantity l/min (depending on tool): 10
- no USB interface
- LCD display
- Adjustable temperature range is tool-dependent: WP 80 / WP 120: 50°C - 450°C (150°F - 850°F) // WSP 150: 50°C - 550°C (150°F - 950°F) // DSX 80 / DXV 80: 50°C - 450°C (150°F - 850°F) // HAP 1: 50°C - 550°C (150°F - 950°C) // DSX 120: 50°C - 450°C (150°F - 850°F)
- negative pressure: 0,7 bar
- Flow rate l/min: 18
- WT compatible

item number	WL26294
model	WR 2000A
model line	WR 2
manufacturer	WELLER
manufacturer item number	T0053378699N
length	280 mm
width	240 mm
height	103 mm
scope of supply	1x WR 2 supply unit 1x hot air piston HAP 1 1x safety support WDH 30 1x hot air nozzle R06, Ø 3.0 mm 1x hot air nozzle R04, Ø 1.2 mm
length in inches	9.45 in
width in inches	11.02 in
height in inches	4.06 in
order unit	1 piece
content unit	1 piece
power	250 W
nominal power	300 W
voltage	230 V
temperature range °C	50 – 550 °C

temperature range °F	150 – 950 °F
temperature accuracy °C	±17 °F
station type	soldering station
included stand	WD
included nozzles	R04, R06
included control unit	WR 2
included handpiece	Hot air piston HAP 1
temperature stability °C	±2 °C
temperature stability °F	±4 °F
number of channels	2
ESD safe	yes

