

## WR 2, digital 2-channel supply unit, 250 W (300 W)



### Rework on highest level

One station meets the requirements of a rework workplace. Unique connecting compatibility of all tools. 2 independent tool channels with automatic tool recognition guarantee the simultaneous operation of 2 soldering tools. Tools are permanently ready for use.

The Weller Rework station WR 2 is a versatile soldering and desoldering station for professional repair work on electronic components of the latest technology in industrial production technology as well as in the repair and laboratory sector. The WR 2 has two independent tool-specific channels with automatic tool recognition and activation. Simultaneous soldering and desoldering or soldering and hot air soldering is thus possible at any time. With the exception of the Weller High-Speed Tools, all soldering tools such as soldering irons, solder baths, desoldering irons or hot air irons can be operated with the rework station.

- 2 independent tool channels with automatic tool recognition

Products for the electronic industry



- Simultaneous use of up to 2 tools
- Overcurrent release: 1.6 A
- IPC compliant: Tip to ground Corresponds to IPC-J-001
- Built-in pump: intermittent operation 30/30 s
- Display: LCD
- equipotential bonding
- WT compatible
- USB interface

<b>item number</b>	<b>WL26390</b>
model	WR 2
model line	WR 2
manufacturer	WELLER
manufacturer item number	T0053377699N
length	280 mm
width	240 mm
height	103 mm
scope of supply	Control unit WR 2
length in inches	11.02 in
width in inches	9.45 in
height in inches	4.06 in
order unit	1 piece
content unit	1 piece
power	300 W
voltage	230 V
air volume max	10 l/min
temperature range °C	50 – 550 °C
temperature range °F	150 – 999 °F
temperature accuracy °F	±17 °F
temperature stability °C	±2 °C
temperature stability °F	±4 °F
vacuum	0.7 Bar
number of channels	2