

Soldering tip SxV series, chisel-shaped 2 x 11 mm



SxV-Solder Tips are the standard soldering tip range for the Metcal PS-900/MFR1100, MFR-2210, MFR-1351-series soldering systems. The temperature/series is designated by the first digit following the dash in the part number. The SFV-series are nominally 390 °C. Metcal recommends the SFV-series for the majority of applications. However, thefamily also offer a higher temperature serie designated SCV, nominally 450 °C, for high temperature and thermally demanding applications. STV-series are nominally 330 °C for light load application. Can be used with leaded and lead-free solder The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

- for temperature sensitive applications
- suitable for the handpieces of PS and MFR systems

item number

WL26470







Products for the electronic industry







model	STV-CH20
manufacturer	OKI
manufacturer item number	STV-CH20
GPSR manufacturer information	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
order unit	1 piece
content unit	1 piece
product series	SxV Series
temperature max.	366 °C
Tip series	SxV
tip length	11 mm
tip width	2 mm
tip shape	chisel-shaped
tip alignment	straight
tip temperature	421 °C
ESD safe	no

Other versions

item number

temperature max. WL26470 366 °C WL24778 421 °C 471 °C WL27828









