

SONOREX SUPER ultrasonic bath 3 litres



SONOREX SUPER baths with 0.9 to 90.0 litres capacity.

The robust and compact SONOREX SUPER ultrasonic baths are characterised by their convenient operability. The size and number of cleaning products or sample vessels determine the selection of the appropriate ultrasonic cleaning bath.

- External dimensions (L x W x H mm): $260 \times 160 \times 250$ mm
- Internal dimensions of oscillating tank (L x W x D mm): 240 × 140 × 100 mm
- Vibration systems
- Ultrasonic frequency 35 kHz
- Time setting 1 15 min, \pm 5 %, continuous operation (∞)

• H types with adjustable temperature range 30 - 80 °C, RK 31 H with heater 65 °C - fixed setting Oscillating tanks made of stainless steel

• RK 102 H with hard-chrome plated oscillating tank, robust stainless steel housing - easy to clean and protected against dripping water

- from RK 102 H the ultrasonic baths have a drain for easy emptying
- Operating voltage 230 V $^{\sim}$ (±10 %), alternatively 115 V $^{\sim}$ (±10 %), 50/60 Hz

Products for the electronic industry





SONOREX SUPER ... CH ultrasonic baths from 45 to 90 litres capacity offer an even longer lifetime due to welded oscillating tank made of stainless steel 1.4404, 2 mm
SONOREX SUPER ultrasonic baths: Medical device class I

item number	WL26692
model	RK 100
manufacturer	BANDELIN
manufacturer item number	301
order unit	1 piece
content unit	1 piece
content in liter	31
nominal power	80 W
Power consumption	0,4 AMPERE
max. ultrasonic power	320 W

Products for the electronic industry

