

## Ionizer SMB60, small table model

---



The mobile, small SMB60 ionization unit from SIMCO neutralizes electrostatic charges at workstations and in the ESD service area. The integrated blower is infinitely adjustable. In the ionizing unit, the ionization is based on high-frequency alternating voltage (HF-AC).

- Neutralisation of electrostatic charges at workplaces and in the service area
- Ionization range: 300 x 900 mm
- Integrated, infinitely adjustable fan
- Ionization based on high frequency alternating voltage (HF-AC)
- Piezoceramic high voltage transducer
- Supply voltage 24 V DC / 100-240 V AC with plug-in power supply unit (included in delivery)
- Self-balancing  $\pm 20V$
- Replaceable air filter
- Ozone generation 0,005 ppm (distance 15 cm)
- Dimensions: 153 x 99 x 65 mm (W x H x D)

|                          |                            |
|--------------------------|----------------------------|
| item number              | WL26782                    |
| model                    | 7520.HF.SMB60              |
| manufacturer             | SIMCO                      |
| manufacturer item number | 7520.HF.SMB60              |
| width                    | 153 mm                     |
| height                   | 99 mm                      |
| depth                    | 65 mm                      |
| order unit               | 1 piece                    |
| content unit             | 1 piece                    |
| supply voltage           | 240 V                      |
| Air Flow                 | stufenlos                  |
| ionic balance            | self-balancing +/- 20 Volt |
| ionization range         | 300 x 900 cm               |
| ozone production         | 0.005 ppm (distance 15 cm) |
| ESD safe                 | yes                        |