

Replacement blade for automatic wire stripper 12 42 195



Replacement blade block for 12 42 195 Stripping without readjustment from 0.03 to 10.0 mm². recessed wire cutter. universal blade geometry - robust and durable. recessed wire cutter. Fully automatic adjustment to all solid, stranded and fine-stranded conductors with standard insulation in the entire capacity range from 0.03 to 10.0 mm². No manual fine adjustment necessary. No damage to the conductors. The steel clamping jaws hold the cable firmly without slipping and without damaging the remaining insulation. With recessed wire cutter for stranded copper and aluminium conductors up to 10 mm² and solid conductors up to 6 mm². Particularly smooth-running mechanism and very low weight. Blade block and length stop interchangeable. Handle with soft plastic zone for secure grip.

- Fully automatic adjustment to all solid, stranded and fine-stranded conductors with standard insulation in the entire capacity range from 0.03 to 10.0 mm².
- No manual fine adjustment necessary
- No damage to the conductors
- The steel clamping jaws hold the cable firmly without slipping and without damaging the remaining insulation

- With recessed wire cutter for stranded Cu and Al conductors up to 10 mm² and solid conductors up to 6 mm²
- Particularly smooth-running mechanics and very low weight
- Replaceable blade block and length stop
- Handle with soft plastic zone for secure grip

item number	WL26968
model	12 49 21
manufacturer	KNIPEX
manufacturer item number	12 49 21
length	84 mm
width	51 mm
height	17 mm
length with packaging	82 mm
width with packaging	50 mm
height with packaging	16 mm
Packaging volume	0.066 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	single pack
RoHS conform	no
VDE	no
ESD safe	no
type of pliers	wire stripper