

Extraction unit Zero Smog 4V Kit 1 nozzle for soldering fumes, incl. Easy-Click 60, 230 m³/h at 2,700 Pa



- Energy-efficient extraction system cleans the air at up to 4 workstations. Nozzle included for applications where a specific area needs to be extracted from above or when there is limited space at the workbench
- Equipped with HEPA H13 particle filter and F7 fine dust pre-filter
- The Constant Flow Control (CFC) function guarantees optimally regulated extraction for each individual workstation, regardless of the number of connected workstations
- Electronic filter control with visual and acoustic alarm function
- Low noise emission levels for quiet working areas
- RS232 port, can be controlled remotely via remote control (optional accessory) or via a PC with RS232 connection
- Efficiency test via USB port
- 4 castors for easy movement of the unit

Item no.	WL27095
Model	ZERO-SMOG-4V Kit 1 Düse
Manufacturer	WELLER
Manufacturer article no.	T0053663699N
GPSR manufacturer data	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller.eu
Length	345 mm
Width	325 mm
Height	505 mm
Scope of delivery	1x extraction unit Zero Smog 4V Kit 2 nozzle 1x compact filter 1x fine dust filter F7 1x Kit 1 WF Slanted nozzle (Easy-Click 60 extraction arm 1.0 m, Easy-Click 60 shut-off valve, Easy-Click 60 extraction hose 3.0 m, Easy-Click 60 slanted nozzle FT-NL) 1x hose connection (straight) 1x operating instructions
Sales unit	1 piece
Content unit	1 piece
Frequency	50/60 Hz
Power	275 W
Voltage	230 V
Vacuum (max.)	3800 Pa
Sound level	48 dBA
Volume flow rate (max.)	230 m ³ /h
Filter type	compact filter
ESD compliant	yes