

Solder fume extractor, Zero Smog 4V Kit 2 Nozzle



- Extraction unit for use at up to 4 workstations
- The Constant Flow Control (CFC) function guarantees optimally regulated extraction for each individual workstation, regardless of the number of workstations connected.
- Electronic filter control with optical and acoustic alarm function
- Efficiency test via USB connection
- 4 castors for flexible use
- Low noise level
- The suction unit ZS 4V Kit 2 nozzle is easy to install and operate. Specially designed as a compact, central system, the kit comes complete with two flexible hoses, hose suction nozzles, suction arms, angled nozzles, valves and brackets and is ready for immediate use at the workplace. A powerful, maintenance-free turbine guarantees continuous smoke extraction with a maximum flow rate of up to 230 m³/h. The CFC function automatically regulates the turbine speed, optimizes the suction power required and reduces energy consumption.
- Remote control via RS 232 connection
- 4 different sets available

item number

WL27096

Products for the electronic industry



model	ZERO-SMOG-4V Kit 2 Düse
manufacturer	WELLER
manufacturer item number	T0053665699N
length	345 mm
width	325 mm
height	505 mm
order unit	1 piece
content unit	1 piece
frequency	50/60 Hz
voltage	230 V
vacuum max	3800 Pa
noise level	48 dBA
volume flow max	230 m ³ /h

