

## Extraction unit Zero Smog 4V Kit 2 nozzle for soldering fumes, incl. Easy-Click 60, 230 m<sup>3</sup>/h at 2,700 Pa



- The Constant Flow Control (CFC) function guarantees optimally regulated extraction for each individual workstation, regardless of the number of connected workstations
- Electronic filter control with visual and acoustic alarm function
- Efficiency test via USB connection
- 4 castors for flexible use
- Remote control via RS 232 connection
- Low noise level
- 4 different sets available

Item no.	WL27096
Model	ZERO-SMOG-4V Kit 2 Düse
Manufacturer	WELLER
Manufacturer article no.	T0053665699N
GPSR manufacturer data	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim

www.weller-tools.com

Length	345 mm
Width	325 mm
Height	505 mm
Scope of delivery	1x extraction unit Zero Smog 4V Kit 2 nozzle 1x compact filter 1x fine dust filter F7 2x Kit 1 WF Slanted nozzle (Easy-Click 60 extraction arm 1.0 m, Easy-Click 60 shut-off valve, Easy-Click 60 extraction hose 3.0 m, Easy-Click 60 slanted nozzle FT-NL) 2x hose connection (straight) 1x instruction manual
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
Frequency	50/60 Hz
Power	275 W
Voltage	230 V
Vacuum (max.)	3800 Pa
Sound level	48 dBA
Volume flow rate (max.)	230 m <sup>3</sup> /h
Filter type	compact filter
ESD compliant	yes