

MultiStrip 10, automatic wire stripper, 0.03 - 10.0 mm², 195 mm



KNIPEX MultiStrip 10 Stripping without readjustment from 0.03 to 10.0 mm². recessed wire cutter. universal blade geometry - robust and durable. optimum handle design with excellent feel. Fully automatic adjustment to all solid, stranded and fine-stranded conductors with standard insulation in the entire capacity range from 0.03 to 10.0 mm². No manual fine adjustment necessary. No damage to the conductors. The steel clamping jaws hold the cable firmly without slipping and without damaging the remaining insulation. With recessed wire cutter for stranded copper and aluminium conductors up to 10 mm² and solid conductors up to 6 mm². Particularly smooth-running mechanism and very low weight. Blade block and length stop interchangeable. Handle with soft plastic zone for secure grip. - Stripping values square millimetres: 0.03 - 10.0mm² - AWG: 32 - 7

standard insulation in the entire capacity range from 0.03 to 10.0 mm²

- No manual fine adjustment necessary
- No damage to the conductors

• The steel clamping jaws hold the cable firmly without slipping and without damaging the remaining insulation

• With recessed wire cutter for stranded Cu and AI conductors up to 10 mm² and solid

Products for the electronic industry





conductors up to 6 mm^2

- Particularly smooth-running mechanics and very low weight
- Replaceable blade block and length stop
- Handle with soft plastic zone for secure grip

item number	WL27245
model	12 42 195
manufacturer	KNIPEX
manufacturer item number	12 42 195
length	190 mm
width	112 mm
height	18 mm
length with packaging	196 mm
width with packaging	121 mm
height with packaging	28 mm
Packaging volume	0.616 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	single pack
product series	MultiStrip 10
RoHS conform	no
VDE	no
ESD safe	no
strip range square millimeter	0.03 – 10 mm ²
AWG	32 - 7
type of pliers	automatic wire stripper

Products for the electronic industry

