

## Soldering tip SxP series, chisel-shaped 30° 2 x 10 mm



SxP-Solder Tip Cartridges are the standard soldering tip range for the Metcal MFR-1110, MFR-2210 and MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The Temperature series SFP are nominally 390 °C. Metcal recommends the SFP-series for the majority of applications. However, the family also offer a higher temperature serie designated SCP, nominally 450 °C, for high temperature and thermally demanding applications. STP-series are nominally 330 °C for light load application. Can be used with leaded and lead-free solder. The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

- suitable for ceramics and applications with high thermal requirements

|          |          |
|----------|----------|
| Item no. | WL27524  |
| Model    | SCP-CH20 |

Products for the electronic industry



|                          |  |
|--------------------------|--|
| Manufacturer             | OKI  |
| Manufacturer article no. | SCP-CH20   |
| GPSR manufacturer data   | OK International Ltd<br>Eagle Close, Chandlers Ford<br>GB-SO53 4NF Hampshire<br>www.ok-international.com |
| Sales unit               | 1 piece  |
| Content unit             | 1 piece  |
| Product series           | SxP Series   |
| Temperature (max.)       | 471 °C   |
| Tip series               | SxP  |
| Angle (soldering tip)    | 30 °   |
| Tip length               | 10 mm  |
| Tip width                | 2 mm   |
| Tip shape                | chisel-shaped  |
| Tip alignment            | bent   |
| Tip temperature          | 460 °C   |
| Matching handpiece       | MFR-H1-SC  |
| ESD compliant            | no   |

## Other versions

| Item no.       | Temperature (max.) |
|----------------|--------------------|
| WL26907        | 366 °C             |
| WL24723        | 421 °C             |
| <b>WL27524</b> | <b>471 °C</b>      |