Soldering tip SxP series, hoof-shaped angled 30°, 0.5 x 15.21 mm



SxP-Solder Tip Cartridges are the standard soldering tip range for the Metcal MFR-1110, MFR-2210 and MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The SFP temperature series are nominally 390 ˚C. Metcal recommends the SFP-series for most applications. However, Metcal offers a higher temperature series designated SCP, nominally 450 ˚C, for high temperature and thermally demanding applications. STP-series are nominally 330 ˚C for light load application. Can be used with leaded and lead-free solder. The Metcal "SmartHeat®-Technology" adjusts power levels automatically based on the demand of the application.
• for temperature sensitive applications

Item no.	WL27536
Model	STP-DRH05

Manufacturer	OKI
Manufacturer article no.	STP-DRH05
GPSR manufacturer data	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Sales unit	1 piece
Content unit	1 piece
Product series	SxP Series
Temperature (max.)	366 °C
Tip series	SxP
Angle (soldering tip)	30 °
Tip length	15.21 mm
Tip width	0.5 mm
Tip shape	angled, hoof-shaped
Tip alignment	bent
Tip temperature	365 °C
Matching handpiece	MFR-H1-SC
ESD compliant	no

Other versions

Item no.	Temperature (max.)
WL27536	**366 °C**
WL24733	421 °C
WL27537	471 °C