

Soldering tip SxP series, hoof-shaped 30°, 1.5 x 16.5 mm



SxP-Solder Tip Cartridges are the standard soldering tip range for the Metcal MFR-1110, MFR-2210 and MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The Temperature series SFP are nominally 390 °C. Metcal recommends the SFP-series for the majority of applications. However, the family also offer a higher temperature serie designated SCP, nominally 450 °C, for high temperature and thermally demanding applications. STP-series are nominally 330 °C for light load application. Can be used with leaded and lead-free solder. The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

- suitable for ceramics and applications with high thermal requirements

| | |
|----------|-----------|
| Item no. | WL27539 |
| Model | SCP-DRH15 |

Products for the electronic industry



| | |
|--------------------------|--|
| Manufacturer | OKI |
| Manufacturer article no. | SCP-DRH15 |
| GPSR manufacturer data | OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com |
| Sales unit | 1 piece |
| Content unit | 1 piece |
| Product series | SxP Series |
| Temperature (max.) | 471 °C |
| Tip series | SxP |
| Angle (soldering tip) | 30 ° |
| Tip length | 16.5 mm |
| Tip width | 1.5 mm |
| Tip shape | hoof-shaped |
| Tip alignment | sloped |
| Tip temperature | 460 °C |
| Matching handpiece | MFR-H1-SC |
| ESD compliant | no |

Other versions

| Item no. | Temperature (max.) |
|----------------|--------------------|
| WL27538 | 366 °C |
| WL24734 | 421 °C |
| WL27539 | 471 °C |