

## Rework tip RxP series blade-shaped 15.6 mm



RxP-Blade/Quad Solder Tip Cartridges are the rework tips for the Metcal MFR-series soldering systems. The second letter in the part number designates the temperature series. RFP-Cartridges are nominally 390 °C. Metcal recommends the RFP temperature series for most applications. However, there is a higher temperature range designated RCP, nominally 450 °C, for high temperature and thermally demanding applications. Can be used with leaded and lead-free solder. The Metcal SmartHeat®-Technology“ will adjust the power levels during soldering to suit the application.

- suitable for ceramics and applications with high thermal requirements
- suitable for MFR-1100 and MFR-220 series

|              |         |
|--------------|---------|
| Item no.     | WL27545 |
| Model        | RCP-BL2 |
| Manufacturer | OKI     |

|                          |                                                                                                          |
|--------------------------|----------------------------------------------------------------------------------------------------------|
| Manufacturer article no. | RCP-BL2                                                                                                  |
| GPSR manufacturer data   | OK International Ltd<br>Eagle Close, Chandlers Ford<br>GB-SO53 4NF Hampshire<br>www.ok-international.com |
| Sales unit               | 1 piece                                                                                                  |
| Content unit             | 1 piece                                                                                                  |
| Incl. battery            | no                                                                                                       |
| Product series           | RxP Series                                                                                               |
| Type of tip              | Rework-Lötklingen                                                                                        |
| Temperature (max.)       | 471 °C                                                                                                   |
| Tip series               | RxP                                                                                                      |
| Tip length               | 9.14 mm                                                                                                  |
| Tip width                | 15.6 mm                                                                                                  |
| Tip thickness            | 0.5 mm                                                                                                   |
| Tip shape                | blade-shaped                                                                                             |
| Tip alignment            | straight                                                                                                 |
| Matching handpiece       | MFR-H1-SC                                                                                                |
| ESD compliant            | no                                                                                                       |

## Other versions

| Item no.       | Tip width      |
|----------------|----------------|
| WL27544        | 10 mm          |
| <b>WL27545</b> | <b>15.6 mm</b> |
| WL27546        | 22.1 mm        |