

Pair of tweezer tips TxP series, angled blade, width 6.35 mm



TxP-Tweezer Tip Cartridges are the standard tweezer tip range for the Metcal MFR-series soldering systems. TFP-Tweezer tips are nominally 390 °C. Metcal recommends the TFP-series for most applications. The TCP Tweezer tips are nominally 450 °C and recommended for high temperature and thermally demanding applications. Can be used with leaded and lead-free solder. The Metcal "SmartHeat®-Technology" adjusts power levels automatically based on the demand of the application.

- suitable for MFR-1100 and MFR-2200
- suitable for ceramics and applications with high thermal requirements

Item no.	WL27565
Model	TCP-BLH40
Manufacturer	OKI
Manufacturer article no.	TCP-BLH40

Products for the electronic industry



GPSR manufacturer data

OK International Ltd
Eagle Close, Chandlers Ford
GB-SO53 4NF Hampshire
www.ok-international.com

Sales unit	1 pair
Content unit	1 pair
Product series	TxP Series
Temperature (max.)	471 °C
Tip series	TxP
Tip dimensions	0,57 x 1,4 mm
Tip width	6.35 mm
Tip shape	angled, blade-shaped
Tip alignment	bent
Tip temperature	460 °C
Matching handpiece	MFR-H4-TW
ESD compliant	no

Other versions

Item no.	Temperature (max.)
WL26218	421 °C
WL27565	471 °C

