

Electric pliers, chrome-plated, Ø 15 mm / 50 mm², 200 mm



Electrical installation pliers 6 functions in one pair of pliers. Multifunctional pliers for electrical installation; for gripping flat and round material, bending, deburring, cable cutting, stripping and crimping wire end ferrules. Smooth gripping surfaces at the tip for damage-free gripping of single wires; profiled gripping surfaces and burner hole for gripping flat and round material. Distinctive outer edge on the gripping surfaces for working on flush-mounted boxes and deburring feed-through holes. Stripping holes for conductors 0.75 - 1.5 mm² and 2.5 mm². Crimping nest for wire end ferrules 0.5 - 2.5 mm². Cable shears with precision cutting edges (inductively hardened) for Cu and Al cables up to 5 x 2.5 mm² / Ø 15 mm. Slim design for good accessibility. Bolted joint: precise, backlash-free operation of the pliers. - Cutting value Cu-cable, stranded: Ø 15mm - Cutting value Cu-cable, stranded: 50mm² - Stripping values for single wires: 0.75 - 1.5mm² / 2.5mm² - Capacity square millimetre: 0.5 - 2.5mm² - AWG: 1 / 0 - VDE-tested: Yes

- Smooth gripping surfaces at the tip for damage-free gripping of single wires
- Profiled gripping surfaces and burner hole for gripping flat and round material
- Distinctive outer edge on the gripping surfaces for working on flush-mounted boxes and deburring feed-through holes
- Stripping holes for conductors 0.75 - 1.5 mm² and 2.5 mm²
- Crimping nest for wire end ferrules 0.5 - 2.5 mm²
- Cable shears with precision cutting edges (inductively hardened) for Cu and Al cables up to 5 x 2.5 mm² / Ø 15 mm
- Slim design for good accessibility
- screwed joint: precise, backlash-free operation of the pliers

| | |
|--------------|-----------|
| Item no. | WL27688 |
| Model | 13 86 200 |
| Manufacturer | KNIPEX |

Products for the electronic industry



| | |
|---|---|
| Manufacturer article no. | 13 86 200 |
| GPSR manufacturer data | KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de |
| Length | 255 mm |
| Width | 85 mm |
| Height | 20 mm |
| Length with packaging | 211 mm |
| Width with packaging | 66 mm |
| Height with packaging | 30 mm |
| Volume with packaging | 3.571 dm ³ |
| Sales unit | 1 piece |
| Content unit | 1 piece |
| Type of packaging | single pack |
| Standards | DIN EN 60900 IEC 60900 |
| RoHS compliant | no |
| Surface | chrome-plated |
| VDE | no |
| Stripping value (single wires) | 0.75 - 1.5 / 2.5 mm |
| Crimp profile | Mandrel crimp |
| ESD compliant | no |
| AWG | 1 / 0 |
| Grip (expression) | Insulated with multi-component sleeves, VDE-tested |
| Cutting value copper cable, stranded | 50 mm ² |
| Cutting value copper cable, stranded (diameter) | 15 mm |
| Type of pliers | manual wire stripper |