

## Electric pliers, chrome-plated, Ø 15 mm / 50 mm<sup>2</sup>, 200 mm



Electrical installation pliers 6 functions in one pair of pliers. Multifunctional pliers for electrical installation; for gripping flat and round material, bending, deburring, cable cutting, stripping and crimping wire end ferrules. Smooth gripping surfaces at the tip for damage-free gripping of single wires; profiled gripping surfaces and burner hole for gripping flat and round material. Distinctive outer edge on the gripping surfaces for working on flush-mounted boxes and deburring feed-through holes. Stripping holes for conductors 0.75 - 1.5 mm<sup>2</sup> and 2.5 mm<sup>2</sup>. Crimping nest for wire end ferrules 0.5 - 2.5 mm<sup>2</sup>. Cable shears with precision cutting edges (inductively hardened) for Cu and Al cables up to 5 x 2.5 mm<sup>2</sup> / Ø 15 mm. Slim design for good accessibility. Bolted joint: precise, backlash-free operation of the pliers. - Cutting value Cu-cable, stranded: Ø 15mm - Cutting value Cu-cable, stranded: 50mm<sup>2</sup> - Stripping values for single wires: 0.75 - 1.5mm<sup>2</sup> / 2.5mm<sup>2</sup> - Capacity square millimetre: 0.5 - 2.5mm<sup>2</sup> - AWG: 1 / 0 - VDE-tested: Yes

- Smooth gripping surfaces at the tip for damage-free gripping of single wires
- Profiled gripping surfaces and burner hole for gripping flat and round material
- Distinctive outer edge on the gripping surfaces for working on flush-mounted boxes and deburring feed-through holes
- Stripping holes for conductors 0.75 - 1.5 mm<sup>2</sup> and 2.5 mm<sup>2</sup>
- Crimping nest for wire end ferrules 0.5 - 2.5 mm<sup>2</sup>
- Cable shears with precision cutting edges (inductively hardened) for Cu and Al cables up to 5 x 2.5 mm<sup>2</sup> / Ø 15 mm
- Slim design for good accessibility
- screwed joint: precise, backlash-free operation of the pliers

item number	WL27688
model	13 86 200
manufacturer	KNIPEX

manufacturer item number	13 86 200
length	255 mm
width	85 mm
height	20 mm
length with packaging	211 mm
width with packaging	66 mm
height with packaging	30 mm
Packaging volume	3.571 dm <sup>3</sup>
order unit	1 piece
content unit	1 piece
type of packaging	single pack
standards	DIN EN 60900   IEC 60900
RoHS conform	no
surface	chrome-plated
VDE	no
Stripping value of single wires	0.75 - 1.5 / 2.5 mm
crimp profile	Mandrel crimp
ESD safe	no
AWG	1 / 0
type of handle	Insulated with multi-component sleeves, VDE-tested
Cutting value copper cable, multistranded	50 mm <sup>2</sup>
Cutting value copper cable, multistranded (diameter)	15 mm
type of pliers	manual wire stripper