

Electric pliers, chrome-plated, Ø 15 mm / 50 mm², 200 mm



Electrical installation pliers 6 functions in one pair of pliers. Multifunctional pliers for electrical installation; for gripping flat and round material, bending, deburring, cable cutting, stripping and crimping wire end ferrules. Smooth gripping surfaces at the tip for damage-free gripping of single wires; profiled gripping surfaces and burner hole for gripping flat and round material. Distinctive outer edge on the gripping surfaces for working on flush-mounted boxes and deburring feed-through holes. Stripping holes for conductors 0.75 - 1.5 mm² and 2.5 mm². Crimping nest for wire end ferrules 0.5 - 2.5 mm². Cable shears with precision cutting edges (inductively hardened) for Cu and Al cables up to 5 x 2.5 mm² / Ø 15 mm. Slim design for good accessibility. Bolted joint: precise, backlash-free operation of the pliers. - Cutting value Cu-cable, stranded: Ø 15mm - Cutting value Cu-cable, stranded: 50mm² - Stripping values for single wires: 0.75 - 1.5mm² / 2.5mm² - Capacity square millimetre: 0.5 - 2.5mm² - AWG: 1 / 0 - VDE-tested: Yes

- Smooth gripping surfaces at the tip for damage-free gripping of single wires
- Profiled gripping surfaces and burner hole for gripping flat and round material
- Distinctive outer edge on the gripping surfaces for working on flush-mounted boxes and deburring feed-through holes
- Stripping holes for conductors 0.75 - 1.5 mm² and 2.5 mm²
- Crimping nest for wire end ferrules 0.5 - 2.5 mm²
- Cable shears with precision cutting edges (inductively hardened) for Cu and Al cables up to 5 x 2.5 mm² / Ø 15 mm
- Slim design for good accessibility
- screwed joint: precise, backlash-free operation of the pliers

item number	WL27688
model	13 86 200
manufacturer	KNIPEX

manufacturer item number	13 86 200
GPSR manufacturer information	KNIPLEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
length	255 mm
width	85 mm
height	20 mm
length with packaging	211 mm
width with packaging	66 mm
height with packaging	30 mm
Packaging volume	3.571 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	single pack
standards	DIN EN 60900 IEC 60900
RoHS conform	no
surface	chrome-plated
VDE	no
Stripping value of single wires	0.75 - 1.5 / 2.5 mm
crimp profile	Mandrel crimp
ESD safe	no
AWG	1 / 0
type of handle	Insulated with multi-component sleeves, VDE-tested
Cutting value copper cable, multistranded	50 mm ²
Cutting value copper cable, multistranded (diameter)	15 mm
type of pliers	manual wire stripper