

Crimping pliers, also for two-hand operation, black oxide finish, for insulated + uninsulated wire end ferrules, 250 mm



For solderless electrical connections. Up to 30 % reduced hand force compared to standard crimping pliers due to lever transmission. Consistently high crimp quality due to precision inserts and positive lock (can be unlocked). Crimp pressure is precisely set (calibrated) at the factory, adjustable. Two-hand operation for easy crimping of large conductor cross-sections. Good handling due to balanced centre of gravity, angled head and ergonomically shaped handles. - Application: insulated + uninsulated wire-end ferrules - Capacity square millimetres: 0.25 - 6mm² - Number of nests: 5 - AWG: 23 - 10

- For solderless electrical connections
- Up to 30 % reduced hand force compared to standard crimping pliers due to lever transmission
- Consistently high crimp quality due to precision inserts and positive lock (can be unlocked)
- Crimping pressure is precisely set (calibrated) at the factory, adjustable
- Two-hand operation for easy crimping of large conductor cross sections
- Good handling due to balanced centre of gravity, angled head and ergonomically shaped handles

item number	WL27696
model	97 52 08
manufacturer	KNIPEX
manufacturer item number	97 52 08

length	250 mm
width	75 mm
height	23 mm
length with packaging	260 mm
width with packaging	100 mm
height with packaging	30 mm
Packaging volume	0.78 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	single pack
RoHS conform	no
surface	burnished
VDE	no
application crimp	insulated + uninsulated ferrules
Number of crimp nests	5
crimp profile	Trapezoidal crimp
tool length	250 mm
AWG	23 - 10
type of handle	with non-slip plastic sleeves
type of pliers	automatic crimping tool