

Crimping pliers, also for two-hand operation, black oxide finish, for insulated + uninsulated wire end ferrules, 250 mm



Description

For solderless electrical connections. Up to 30 % reduced hand force compared to standard crimping pliers due to lever transmission. Consistently high crimp quality due to precision inserts and positive lock (can be unlocked). Crimp pressure is precisely set (calibrated) at the factory, adjustable. Two-hand operation for easy crimping of large conductor cross-sections. Good handling due to balanced centre of gravity, angled head and ergonomically shaped handles. - Application: insulated + uninsulated ferrules - Capacity square millimetres: 35 - 50mm² - Number of nests: 2 - AWG: 2 / 0

- For solderless electrical connections
- Up to 30 % reduced hand force compared to standard crimping pliers due to lever transmission
- Consistently high crimp quality due to precision inserts and positive lock (can be unlocked)
- Crimping pressure is precisely set (calibrated) at the factory, adjustable
- Two-hand operation for easy crimping of large conductor cross sections
- Good handling due to balanced centre of gravity, angled head and ergonomically shaped handles

Product details

item number	WL27699
model	97 52 19
manufacturer	KNIPEX
manufacturer item number	97 52 19

Products for the electronic industry



dimensions (LxWxH)	250 mm x 65 mm x 23 mm
dimensions with packaging (LxWxH)	260 mm x 75 mm x 30 mm
Packaging volume	0.585 dm ³
order unit	piece
type of packaging	single pack
RoHS conform	no
surface	burnished
application crimp	insulated + uninsulated ferrules
VDE	no
Number of crimp nests	2
crimp profile	Trapezoidal indent crimp
tool length	250 mm
AWG	2 / 0
type of handle	with non-slip plastic sleeves
type of pliers	automatic crimping tool