

## Crimping pliers, also for two-hand operation, black oxide finish, uninsulated cable lugs + cable connector, 250 mm



For solderless electrical connections. Up to 30 % reduced hand force compared to standard crimping pliers due to lever transmission. Consistently high crimp quality due to precision inserts and positive lock (can be unlocked). Crimp pressure is precisely set (calibrated) at the factory, adjustable. Two-hand operation for easy crimping of large conductor cross-sections. Good handling due to balanced centre of gravity, angled head and ergonomically shaped handles. - Application: uninsulated cable lugs + cable connectors - Capacity square millimetres: 16 / 25mm² - Number of nests: 2 - AWG: 5 / 3

- For solderless electrical connections
- Up to 30 % reduced hand force compared to standard crimping pliers due to lever ratio
- Consistently high crimp quality due to precision inserts and positive lock (can be unlocked)
- Crimping pressure is precisely set (calibrated) at the factory, adjustable
- Two-hand operation for easy crimping of large conductor cross sections
- Good handling due to balanced centre of gravity, angled head and ergonomically shaped handles

item number	WL27700
model	97 52 23
manufacturer	KNIPEX
manufacturer item number	97 52 23
length	255 mm
width	79 mm

Products for the electronic industry













height	24 mm
length with packaging	260 mm
width with packaging	100 mm
height with packaging	30 mm
Packaging volume	$0.78~\mathrm{dm^3}$
order unit	1 piece
content unit	1 piece
type of packaging	single pack
RoHS conform	no
surface	burnished
surface VDE	burnished no
VDE	no
VDE application crimp	no uninsulated cable lugs + cable connectors
VDE application crimp Number of crimp nests	no uninsulated cable lugs + cable connectors 2
VDE application crimp Number of crimp nests crimp profile	no uninsulated cable lugs + cable connectors  2 Mandrel crimp narrow
VDE application crimp Number of crimp nests crimp profile tool length	no uninsulated cable lugs + cable connectors  2 Mandrel crimp narrow 250 mm







