

## Self-adjusting crimping pliers for end sleeves (ferrules) with side entry, black oxide finish, 180 mm



Crimping pliers for wire end ferrules with smaller grip width. For crimping wire end ferrules according to DIN 46228 part 1 + 4. Self-adjusting adjustment to the desired size of the wire end ferrules. Consistently high crimp quality due to positive lock (can be unlocked). Crimp pressure is precisely set (calibrated) at the factory. Force amplification through toggle lever for fatigue-free operation. High operating comfort due to handy design and low weight. Square crimping also for wire end ferrules up to 16 mm $^2$ . Square crimping for optimum contact surfaces in the terminal connection. especially suitable for all twin wire-end ferrules up to 2 x 6 mm $^2$  or 2 x AWG 8. - Application: Wire end ferrules - Capacity square millimetres: 0.08 - 10 / 16mm $^2$  - Number of nests: 1 - AWG: 28 - 5.

- For crimping ferrules according to DIN 46228 part 1 + 4
- Self-adjusting adjustment to the desired ferrule size
- Consistently high crimp quality due to positive lock (can be unlocked)
- Crimping pressure is precisely set (calibrated) at the factory
- Force amplification through toggle lever for fatigue-free operation
- High operating comfort due to handy design and low weight

item number	WL27/04
model	97 53 04
manufacturer	KNIPEX
manufacturer item number	97 53 04

Products for the electronic industry













length	175 mm
width	77 mm
height	21 mm
length with packaging	235 mm
width with packaging	75 mm
height with packaging	20 mm
Packaging volume	0.353 dm <sup>3</sup>
order unit	1 piece
content unit	1 piece
type of packaging	single pack
RoHS conform	no
surface	burnished
VDE	no
application crimp	Wire end ferrules
Number of crimp nests	1
crimp profile	Square crimp automatic
tool length	180 mm
AWG	28 - 5
type of handle	with multi-component sleeves
type of pliers	automatic crimping tool







