

Crimping pliers for end sleeves (ferrules), plastic-coated handles, 0.25 - 16.0 mm², 180 mm



Crimping pliers for wire end ferrules light and slim design. also available as VDE version. easy crimping due to optimised transmission ratio. For crimping wire end ferrules according to DIN 46228 part 1 + 4 in the range of 0.25 to 16 mm². Crimping in marked half-round profiles for secure connection of sleeve and conductor. Nine particularly deep profiles with conical side surfaces. - Application: Ferrules - Capacity square millimetres: 0.25 - 16.0mm² - Number of nests: 9 - AWG: 23 - 5.

- For crimping wire end ferrules according to DIN 46228 part 1 + 4 in the range of 0,25 to 16 mm².
- Crimping in marked half-round profiles for secure connection of sleeve and conductor
- Nine particularly deep profiles with conical side surfaces

Item no.	WL27708
Model	97 71 180
Manufacturer	KNIPEX
Manufacturer article no.	97 71 180
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	185 mm
Width	49 mm
Height	15 mm
Length with packaging	230 mm

Width with packaging	83 mm
Height with packaging	48 mm
Volume with packaging	0.924 dm ³
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
RoHS compliant	no
VDE	no
Crimping application	Wire end ferrules
Number of crimp nests	9
Crimp profile	Mandrel crimp narrow
ESD compliant	no
Tool length	180 mm
AWG	23 - 5
Grip (expression)	coated with plastic
Type of pliers	manual crimping tool