


Soldering tip SxV series, knife-shaped 45°, 5 x 15.1 mm



SxV-Solder Tips are the standard soldering tip range for the Metcal PS-900/MFR1100, MFR-2210, MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The temperature series SFV are nominally 390 °C. Metcal recommends the SFV-series for the majority of applications. However, the family also offer a higher temperature serie designated SCV, nominally 450 °C, for high temperature and thermally demanding applications. STV-series are nominally 330 °C for light load application. Can be used with leaded and lead-free solder The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

- suitable for ceramics and applications with high thermal requirements
- suitable for the handpieces of PS and MFR systems

item number	WL27920
model	SCV-DRK45A
manufacturer	OKI
manufacturer item number	SCV-DRK45A
GPSR manufacturer information	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
order unit	1 piece
content unit	1 piece
product series	SxV Series

Products for the electronic industry



temperature max.	471 °C
Tip series	SxV
Soldering tip angle	45 °
tip dimensions	5 x 2,4 mm
tip length	15.1 mm
tip width	5 mm
tip shape	knife-shaped
tip alignment	bent
tip temperature	460 °C
ESD safe	no

Other versions

item number	temperature max.
WL27920	471 °C