

Soldering tip SxP series, hoof-shaped 60°, 1.5 x 11.6 mm



SxP-Solder Tip Cartridges are the standard soldering tip range for the Metcal MFR-1110, MFR-2210 and MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The SFP-series are nominally 390 °C. Metcal recommends the SFP-series for the majority of applications. However, the family also offer a higher temperature series designated SCP, nominally 450 °C, for high temperature and thermally demanding applications. STP-series are nominally 330 °C for light load application. Can be used with leaded and lead-free solder. The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

for most standard applications

item number WL27926

model SFP-DRH615















manufacturer	OKI
manufacturer item number	SFP-DRH615
GPSR manufacturer information	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
order unit	1 piece
content unit	1 piece
product series	SxP Series
temperature max.	421 °C
Tip series	SxP
Soldering tip angle	60 °
tip length	11.6 mm
tip width	1.5 mm
tip shape	hoof-shaped
tip alignment	sloped
tip temperature	421 °C
suitable handle	MFR-H1-SC
ESD safe	no

Other versions

item number temperature max.

WL27926 421 °C









