

CCV series soldering tip, blade-shaped, 10 mm



CxV-Solder Blades are part of the rework soldering tips for the Metcal PS-900/MFR-1120, MFR-2220-series soldering systems. The second letter of the part number designates the temperature series. The CFV temperature series is nominally 390 °C. Metcal recommends the CFV temperature series for most applications. However, there is a higher temperature range designated CCV, nominally 450 °C, for high temperature and thermally demanding applications. Can be used with leaded and lead-free solder. The Metcal "SmartHeat® Technology" automatically adjusts power levels during each soldering operation.

- suitable for ceramics and applications with high thermal requirements
- suitable for the MFR system

Item no.	WL27999
Model	CCV-BL100
Manufacturer	OKI

Manufacturer article no.	CCV-BL100
GPSR manufacturer data	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
Product series	CxV Series
Type of tip	Rework-Lötklingen
Temperature (max.)	471 °C
Tip series	CxV
Tip dimensions	9,1 x 0,5 mm
Tip length	9.1 mm
Tip width	10 mm
Tip thickness	0.5 mm
Tip shape	blade-shaped
Tip alignment	straight
Tip temperature	460 °C
Matching handpiece	MFR-H2-ST
ESD compliant	no

Other versions

Item no.	Temperature (max.), Tip width
WL27999	471 °C, 10 mm
WL28002	471 °C, 25 mm
WL28005	471 °C, 35 mm
WL28008	471 °C, 40 mm
WL28011	471 °C, 50 mm