

ESD LED magnifier lamp TEVISIO - RLLQ 48/2 AR, 3.5 dpt.



As the No. 1 in mobility and vision quality, Waldmann's TEVISIO ESD LED magnifier lamp is irreplaceable where the highest demands are placed on vision. Now Waldmann brings a new generation of the best magnifier luminaire for the electronics industry. What remains is the innovative rod technology and the perfect lighting concept of the Tevisio magnifier luminaire from Waldmann. Brand new are the higher color rendering value and the more homogeneous light distribution. Particularly noteworthy is the tool-free removal of the lens for cleaning, replacement or exchange. The optional new 6 dpt. plastic lens allows a higher magnification factor at any time if desired. It also impresses with very high color rendering values, absolutely homogeneous light distribution, optimum support for evaluating and verifying color and surface qualities, and with a perfectly clouded aperture that prevents disturbing reflections.

- Control gear: Electronic plug-in ballast
- Connected loads: 100-240 V, 50/60 Hz
- Technology: multi-stage switchable, infinitely dimmable
- Operation: Multifunction push-button

- luminaire housing: plastic, ESD version
- Lamp cover: Lens cover, matt, polyamide (PA)
- Luminaire linkage: aluminium profile, ESD paint finish
- Joint relief: Spring
- Mains connection cable: approx. 3.6 m; mains plug, BS 1363, CEE 7/XVI, NEMA 1-15P
- Mounting: Screw-on flange, base
- Lens: 160 mm diameter, 3.5 dioptries, glass
- no additional lens
- Special feature: ESD version, light characteristics can be influenced by three-step switch
- Em: 4986 lx, Emax: 7503 lx, Emin: 1788 lx (measuring distance: 15 cm)

Article no.	WL28306
Model	RLLQ 48/2 AR
Manufacturer	WALDMANN
Manufacturer article no.	113986000-00766281
GPSR manufacturer data	WALDMANN Lichttechnik Peter-Henlein-Straße 5 DE-78056 Villingen-Schwenningen www.waldmann.com
Length	760 mm
Width	390 mm
Depth	190 mm
Sales unit	1 piece
Content unit	1 piece
Diopters	3.5 dpt
Lamp or magnifying glass type	Magnifying lamp
Luminous flux	750 lm
Connection values	100-240 V, 50/60 Hz
Dimmable	yes
Colour temperature	4000 °K
Power	16 W
Magnification	3.5 Dioptres
Equipping	LED, energy efficiency class A+
Fastening	Pedestal, Table mounting
Case colour	black
Protection class	2
Protection class	20 IP

ESD compliant

yes

