

Solder fume extractor, Zero Smog 4V Kit 2 funnel



- Extraction unit for use at up to 4 workstations
- The Constant Flow Control (CFC) function guarantees optimally regulated extraction for each individual workstation, regardless of the number of workstations connected.
- Electronic filter control with optical and acoustic alarm function
- Efficiency test via USB connection
- 4 castors for flexible use
- Low noise level
- Remote control via RS 232 connection
- 4 different sets
- The Zero Smog 4V Kit 2 funnel suction unit is easy to install and operate. Specially designed as a compact central system, the kit comes complete with two flexible hoses, hose connections, suction arms, funnel nozzles, valves and brackets and is ready for immediate use at the workplace. A powerful, maintenance-free turbine guarantees continuous smoke extraction with a maximum flow rate of up to 230 m³/h. The CFC function automatically regulates the turbine speed, optimizes the suction power required and reduces energy consumption.

item number

WL28360

Products for the electronic industry



model	ZERO-SMOG-4V-KIT2-Trichter
manufacturer	WELLER
manufacturer item number	T0053664699N
length	345 mm
width	325 mm
height	505 mm
scope of supply	1x T0058735936N Compact filter Zero Smog 4V 1x T0058735938 Fine dust filter F7 1x T0058762767N Hose connection, straight 2x T0053657199N Kit 1 WF Funnel
order unit	1 piece
content unit	1 piece
frequency	50/60 Hz
fuse	T1,6A
voltage	230 V
vacuum max	3800 Pa
noise level	48 dBA
volume flow max	230 m ³ /h