

ESD low shoe alu-tec 100 2.0, S2, smooth leather, unisex, black, size 46



At ATLAS®, only the best quality cowhides are processed. Extremely careful selection ensures that only flawless, high-quality and soft leathers are used. The ATLAS Waterproof smooth leather has to withstand special challenges throughout the entire working day. The approx. 2mm thick full-grain cowhide leather is particularly characterised by its lasting waterproofness and thus ensures dry feet for several hours. It is also particularly breathable, durable and dimensionally stable.

ATLAS® brings together state-of-the-art technologies and the anatomical needs of every wearer. The new INNOFLEX SYSTEM® is a holistic running sole concept and supports the runner in every phase of movement. From the first to the last contact with the ground, the sole complex is permanently guided by the same, natural line of force, the INNOFLEX LINE. It optimally guides the forces from the heel to the toe and thus supports the natural line of force progression. Special areas such as the CLOUDZONE in the heel are

responsible for the corresponding energy absorption, i.e. cushioning. The large-format tread surfaces, which are equipped with particularly energy-absorbing MPU® material, absorb the energy and return it to the movement process in a targeted manner. This guarantees fatigue-free walking throughout the entire working day.

Alu-tec® technology: The new lightness. Aluminium has not only served as a high-tech material in aviation and the automotive industry for years, but also in many ATLAS safety shoes today. The anatomically shaped aluminium toe cap is particularly light and shifts the centre of gravity of the shoe to the middle of the foot. This actively helps to prevent tripping accidents caused by imbalance. The thermally neutral behaviour of aluminium also prevents cold bridges from forming inside the shoe and thus guarantees a pleasant foot climate in all seasons.

Particularly in everyday working life, with high physical stress, temperature-regulating properties are not only required, but expected. The aktiv-X functional lining stands for the highest quality, innovative technology and offers the wearer permanent, active moisture regulation. The aktiv-X functional lining regulates moisture and ensures that the shoes dry again quickly. It does not stain, is skin-friendly and abrasion-resistant.

Work healthier with the right cushioning. The new 3D cushioning system from ATLAS® enables noticeably gentle and fatigue-free walking. The basis for this outstanding walking comfort is formed by three basic components: Pressure relief. Cushioning. Dynamics. This is ensured by the perfect interaction of a pressure-relieving insole and the light and responsive MPU sole technology.

geeignet für die Einlagenversorgung-DGUV 112-191

ATLAS® offers you a wide range of different orthopaedic insoles. The articles marked here are suitable for orthopaedic insoles according to DGUV regulation 112-191. The marking on the shoe is decisive for this.

- EN ISO 20345 S2 SRC
- ESD equipment
- Standard width W10, also available in W12 (extra wide)
- suitable for insole supply (DGUV 112-191/BGR 191)

item number	WL28478
model	alu-tec 100 2.0 ESD
model line	alu-tec 100 2.0 ESD
manufacturer	ATLAS
manufacturer item number	12100-46
length with packaging	350 mm

Products for the electronic industry



width with packaging	250 mm
height with packaging	150 mm
order unit	1 pair
content unit	1 pair
colour manufacturer	black
Colour	black
material	Waterproof smooth leather
gender	unisex
protective cap	yes
shoe execution	low shoe
safety class	S2
shoe sole	MPU INNOFLEX system
Slip resistance	SRC
shoe width	W10 (standard width)
features shoes	<ul style="list-style-type: none"> • Waterproof smooth leather • MPU INNOFLEX system • alu-tec aluminium toe cap • aktiv-X functional lining • 3D cushioning system • suitable for insoles-DGUV 112-191
material shoes	waterproof smooth leather
shoe size EU	46
ESD safe	yes
Category (PPE Regulation)	Category 2

Other versions

item number	shoe size EU	shoe width
WL28478	46	W10 (standard width)