

System luminaire TAMETO - SAHQ 88 R, mounting top/fixed, dimmable, 4000 K



The Tameto system luminaire from Waldmann is convincing on many levels: Maintenance-free LED technology, extremely homogeneous, glare-free and flicker-free light as well as light emission with a cone prism structure for perfect glare control. The Tameto system luminaire is available in various lengths for different desk widths and lighting requirements to equip the perfect industrial workplace. The robust aluminium housing and enclosed design protect the inside of the system luminaire and work surface from contamination.

- Control gear: Electronic ballast
- Connected loads: 220-240 V, 50/60 Hz
- Luminous flux: 2900 lm
- Luminaire light yield: approx. 87 lm/W
- Light colour: neutral white
- Colour rendering (Ra): >80
- glare control: conical prismatic diaphragm
- Technique: infinitely dimmable
- Operation: Rocker switch
- Mains connection cable: approx. 3 m; mains plug CEE 7/VII
- Mounting: screw-on tab
- Length: 1256 mm
- Em: 1071 lx, Emax: 1448 lx, Emin: 659 lx

Item no.	WL28559
Model	SAHQ 88 R
Manufacturer	WALDMANN
Manufacturer article no.	112980000-00551364
GPSR manufacturer data	WALDMANN Lichttechnik

Products for the electronic industry



Peter-Henlein-Straße 5
 DE-78056 Villingen-Schwenningen
 www.waldmann.com

Length	1300 mm
Width	220 mm
Depth	120 mm
Sales unit	1 piece
Content unit	1 piece
Lamp or magnifying glass type	workplace light
Luminous flux	2900 lm
Connection values	220-240 V; 50/60 Hz
Colour temperature	4000 °K
Power	33 W
Equipping	LED, energy efficiency class A+
Fastening	Ceiling mounting
Case colour	Aluminium/plastic, anodised, aluminium coloured (colourless anodised)
Protection class	1
Protection class	20 IP
ESD compliant	no