

ESD screwdriver slot 1578 A ESD Micro, 0.25 x 1.2 x 40 mm



Other versions

| item number | blade width | blade thickness | blade length |
|-------------------------|-------------|-----------------|--------------|
| WL28600 | | 1.5 mm | 0.23 mm |
| WL28603 | | 1.8 mm | 0.3 mm |
| WL28601 | | 1.2 mm | 0.25 mm |
| WL28604 | | 2 mm | 0.4 mm |
| WL28605 | | 2.5 mm | 0.4 mm |
| WL28606 | | 3 mm | 0.5 mm |
| WL28607 | | 3.5 mm | 0.6 mm |
| WL28608 | | 4 mm | 0.8 mm |

Description

- Kraftform Micro Screwdriver for slotted screws
- Electrostatically safe tool due to surface resistance of $< 10^9$ Ohm
- Multi-component Kraftform Micro Handle for fast and ergonomic screw fastening
- With roll-off protection and rotating cap for fast twirling
- The Wera Black Point tip offers a perfect fit and optimized corrosion protection.

Product details

| | |
|-----------------------------------|------------------------|
| item number | WL28601 |
| model | 1578a 0,25x1,2 mm |
| manufacturer | WERA |
| manufacturer item number | 05030100001 |
| dimensions (LxWxH) | 157 mm x 13 mm x 13 mm |
| dimensions with packaging (LxWxH) | 174 mm x 64 mm x 34 mm |

Products for the electronic industry



| | |
|---------------------|---------------------|
| order unit | piece |
| ESD safe | yes |
| type of screw | slot |
| type of screwdriver | normal screwdrivers |
| VDE | no |
| packaging mass | piece |
| tool length | 157 mm |
| blade length | 40 mm |
| blade width | 1.2 mm |
| blade thickness | 0.25 mm |