

ESD screwdriver, slotted 1578 A ESD Micro, 0.40 x 2.5 x 80 mm



Other versions

item number	blade width	blade thickness	blade length
WL28600		1.5 mm	0.23 mm
WL28603		1.8 mm	0.3 mm
WL28601		1.2 mm	0.25 mm
WL28604		2 mm	0.4 mm
WL28605		2.5 mm	0.4 mm
WL28606		3 mm	0.5 mm
WL28607		3.5 mm	0.6 mm
WL28608		4 mm	0.8 mm

Description

- Kraftform Micro Screwdriver for slotted screws
- Electrostatically safe tool due to surface resistance of $<10^9$ Ohm
- Multi-component Kraftform Micro Handle for fast and ergonomic screw fastening
- With roll-off protection and rotating cap for fast twirling
- The Wera Point tip offers a perfect fit and optimized corrosion protection.

Product details

item number	WL28605
model	1578a 0,4x2,5 mm
manufacturer	WERA
manufacturer item number	05030104001
dimensions (LxWxH)	177 mm x 13 mm x 13 mm

Products for the electronic industry



dimensions with packaging (LxWxH)	189 mm x 64 mm x 38 mm
scope of supply	0.40x2.5x80
order unit	piece
packaging mass	piece
type of screw	slot
VDE	no
type of screwdriver	normal screwdrivers
ESD safe	yes
tool length	177 mm
handle length	97 mm
blade diameter	2.5 mm
blade length	80 mm
blade length in inches	3.125 in
blade width	2.5 mm
blade thickness	0.4 mm