

## ESD screwdriver, slotted, 0.40 x 2.5 x 80 mm



Electrostatic-protected micro screwdriver. Reliable protection against electrostatic energy and associated damage. Lightning-fast twirling is possible by resting the hand on the rotating cap and thanks to the fast-turning zone underneath the rotating cap. No more time-consuming regripping. Power zone with integrated soft zones ensures the transmission of high loosening and tightening torques. Precision zone for the correct angle of rotation for adjustment work. The Black Point tip offers a precise fit and optimized corrosion protection. Take it easy tool finder with color coding according to profiles and size stamping - for finding the required tool quickly and easily.

- Kraftform Micro screwdriver for slotted screws
- Electrostatic safe tool due to surface resistance of  $<10^9$  Ohm
- Multi-component Kraftform Micro handle for fast and ergonomic screwdriving
- With anti-roll protection and rotating cap for fast twirling
- The Wera Point tip offers a precise fit and optimized corrosion protection

<b>Item no.</b>	<b>WL28605</b>
Model	1578 A ESD Kraftform Micro
Manufacturer	WERA
Manufacturer article no.	05030104001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	177 mm
Width	13 mm
Height	13 mm
Length with packaging	189 mm
Width with packaging	64 mm
Height with packaging	38 mm
Scope of delivery	0.40x2.5x80
Sales unit	1 piece

Content unit	1 piece
VDE	no
Screw type	slot
ESD compliant	yes
Packaging dimensions	piece
Screwdriver type	normal screwdrivers
Tool length	177 mm
Handle length	97 mm
Blade diameter	2.5 mm
Blade length	80 mm
Blade length in inches	3.125 in
Blade width	2.5 mm
Blade thickness	0.4 mm

## Other versions

Item no.	Blade length	Blade width	Blade thickness
WL89373	40 mm	0.8 mm	0.16 mm
WL28601	40 mm	1.2 mm	0.25 mm
WL89374	40 mm	2.5 mm	0.35 mm
WL28603	60 mm	1.8 mm	0.3 mm
WL28604	60 mm	2 mm	0.4 mm
<b>WL28605</b>	<b>80 mm</b>	<b>2.5 mm</b>	<b>0.4 mm</b>
WL28606	80 mm	3 mm	0.5 mm
WL28607	80 mm	3.5 mm	0.6 mm
WL28608	80 mm	4 mm	0.8 mm