

## Solder wire Sn60Pb39Cu1, 1.0 mm / C3



- Flux type C 3: Halogen-free flux for all electronic applications
- 1 blessed

|                          |                                                                                         |
|--------------------------|-----------------------------------------------------------------------------------------|
| <b>Item no.</b>          | <b>WL30684</b>                                                                          |
| Model                    | Flussmitteltyp C3                                                                       |
| Manufacturer             | TAMURA ELSOLD                                                                           |
| Manufacturer article no. | RÖLOT0913                                                                               |
| GPSR manufacturer data   | TAMURA DEUTSCHLAND GmbH<br>Hüttenstraße 1<br>DE-38871 Ilsenburg<br>www.tamura-elsold.de |
| Sales unit               | 1 rolls                                                                                 |
| Content unit             | 1 rolls                                                                                 |

Products for the electronic industry



|                           |                                                                                         |
|---------------------------|-----------------------------------------------------------------------------------------|
| Detail content unit       | 1 kg                                                                                    |
| Incl. battery             | no                                                                                      |
| Flux class                | 1.1.3, F-SW32, ROL0                                                                     |
| Alloy                     | Sn60Pb39Cu1                                                                             |
| Flux type                 | C3                                                                                      |
| Flux content              | 3.5 %                                                                                   |
| Classification            | <ul style="list-style-type: none"><li>• ROL0</li><li>• 1.1.3</li><li>• F-SW32</li></ul> |
| Wire diameter             | 1 mm                                                                                    |
| Alloy                     | Sn60Pb39Cu1                                                                             |
| Lead-free/lead-containing | containing lead                                                                         |