

Solder fume extractor, Zero Smog 4V Kit 1 funnel



- Extraction unit for use at up to 4 workstations
- The Constant Flow Control (CFC) function guarantees optimally regulated extraction for each individual workstation, regardless of the number of workstations connected.
- Electronic filter control with optical and acoustic alarm function
- Efficiency test via USB connection
- 4 castors for flexible use
- Low noise level
- The Zero Smog 4V Kit 1 funnel suction unit is easy to install and operate. Specially designed as a compact, central system, the kit comes complete with a flexible hose, suction arm, funnel nozzle, valve and bracket and is ready for immediate use at the workplace. A powerful, maintenance-free turbine guarantees continuous smoke extraction with a maximum flow rate of up to 230 m³/h. The CFC function automatically regulates the turbine speed, optimizes the suction power required and reduces energy consumption.
- Remote control via RS 232 connection
- 4 different sets available

- Compact filter: particle filter H13, broadband gas filter (50% activated carbon / 50% chemisorb)
- Prefilter: Fine dust filter class F7

| | |
|--------------------------|-----------------------------|
| item number | WL30713 |
| model | ZERO-SMOG-4V Kit 1 Trichter |
| manufacturer | WELLER |
| manufacturer item number | T0053662699N |
| length | 345 mm |
| width | 325 mm |
| height | 505 mm |
| order unit | 1 piece |
| content unit | 1 piece |
| frequency | 50/60 Hz |
| fuse | T1,6A |
| voltage | 230 V |
| vacuum max | 3800 Pa |
| noise level | 48 dBA |
| volume flow max | 230 m ³ /h |