

Solder fume extractor, Zero Smog 6V



- 4 castors for flexible use
- Extraction unit for use at up to 8 workstations
- The Constant Flow Control (CFC) function guarantees optimally regulated extraction for each individual workstation, regardless of the number of workstations connected.
- Electronic filter monitoring with optical and acoustic filter alarm.
- Efficiency test via USB connection
- Low noise level
- Remote control via RS 232 interface
- The Zero Smog 6V suction unit is extremely user-friendly, both in its simple and quick installation and when changing filters. It has a low noise emission and is compact enough to be installed directly at the work area. The high-quality components used keep maintenance costs low and increase the service life. The unit is equipped with automatic speed control (CFC) to extend filter life and energy efficiency. This works independently of the number of connected workstations. To increase the filter capacity, an external prefilter can be connected to the ZS 6V. The powerful, maintenance-free variable speed turbine is

electronically controlled.

item number	WL30714
model	ZERO-SMOG-6V
manufacturer	WELLER
manufacturer item number	T0053666699N
length	460 mm
width	460 mm
height	655 mm
order unit	1 piece
content unit	1 piece
frequency	50/60 Hz
fuse	T3, 15A
voltage	230 V
vacuum max	3000 Pa
noise level	51 dBA
volume flow max	615 m ³ /h

