

Zero Smog 6V extraction unit for soldering fumes, 1-8 workstations, incl. Easy-Click 60, 615 m³/h at 3000 Pa



- Powerful extraction unit cleans the air at up to 8 workstations
- Equipped with HEPA H13 particle filter and F7 fine dust pre-filter
- The Constant Flow Control (CFC) function guarantees optimally regulated extraction for each individual workstation, regardless of the number of connected workstations
- 3 operating modes: Standard speed control: User-selectable regardless of the system load Speed limitation control: The speed is automatically adjusted to the system load Economic regulation: The rate of fume absorption is kept at a constant value
- Electronic filter control with visual and audible filter alarm
- · Low noise emission levels for quiet working areas
- RS232 port, can be remotely controlled by remote control (optional accessory) or by a PC with RS232 connection
- Max. Fan capacity 615 m³/h
- Efficiency test via USB port







Products for the electronic industry





26.04.2025



item number	WL30714
model	ZERO-SMOG-6V
manufacturer	WELLER
manufacturer item number	T0053666699N
GPSR manufacturer information	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller.eu
length	460 mm
width	460 mm
height	655 mm
scope of supply	1x Zero Smog 6V extraction unit 1x compact filter 1x fine dust filter F7 1x hose connection (straight) 1x operating instructions
order unit	1 piece
content unit	1 piece
frequency	50/60 Hz
power	460 W
fuse	T3, 15A
voltage	230 V
vacuum max	3000 Pa
noise level	51 dBA
volume flow max	615 m ³ /h
filter type	compact filter
ESD safe	yes







