

WXR 3031, 3-channel rework station 420 W (600 W)



Everything - and more.

The WXR3 Rework station is the perfect solution for all soldering, desoldering and hot-air jobs. The WXR3 can handle the most demanding tasks but is also ideal for standard jobs. All units can cope with major manufacturing tasks quickly and surely thanks to their straight-forward settings. The station can also be integrated into a traceability process.

600 Watts – unique

The WXR 3 is a 3-channel station with a total output of 600 W. The multifunctional WXR 3 is suitable for all applications, and can work with all WX tools.

Two integrated pumps (self-contained)

A pair of integrated pumps make the system independent of a separate compressed air supply. A high-performance pump for vacuum and hot air, and a separate vacuum pump for pick-up tools.

Automatic / intelligent power management

The rework station provides 600 watts of power. Its intelligent power management function allows the available power to be distributed to the connected tools as required – a total of 600 watts. High-performance tools can be operated at the same time. 3

Products for the electronic industry



channels, 200 watts each.

User-friendly and easy to navigate

The LCD display shows all connected tools. Special functions can easily be set at the press of a button.

- Built-in pump: intermittent operation 30/30 s
- Display: 240 x 88 dots / backlight
- USB interface for firmware update, parameterization and monitoring; any commercially available USB memory stick fits into the USB interface
- Overcurrent release: 2.0 A
- IPC compliant
- WX compatible

Item no.	WL30833
Model	T0053502699
Model line	WXR 3
Manufacturer	WELLER
Manufacturer article no.	T0053502699N
GPSR manufacturer data	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller.eu
Length	273 mm
Width	235 mm
Height	102 mm
Scope of delivery	1x WXR 3 supply unit 1 set of hot air pistons WXHAP 200, including safety rest 1 set desoldering iron WXDP 120, including safety rest 1 set of WXP 120 soldering irons, including safety rest 1x WVP vacuum pipette 1x desoldering nozzle pliers PDN 1x mains plug 1x operating instructions
Length in inches	10.75 in
Width in inches	9.25 in
Height in inches	4.02 in
Sales unit	1 piece
Content unit	1 piece
Power	420 W

Products for the electronic industry



Voltage	230 V
Vacuum	max. 0,7 bar
Temperature range °C	100 – 450 °C
Temperature range °F	200 – 850 °F
Temperature accuracy °F	±17 °F
Station (type)	rework station
Temperature stability °C	±2 °C
Temperature stability °F	±4 °F
Number of channels	3
ESD compliant	yes