

## WXMP MS Set, micro soldering iron with safety rest, 40 W, Active-Tip technology

---



Production within the electronics, medical technology and aerospace industries is moving faster as components become smaller, more sensitive, complex and more powerful. The soldering industry is not different. With the Weller RT MS tips you meet these increasing demands and provide maximum protection to the printed circuit board and the component you're soldering. With the MS tips you achieve the best results and keep your operation costs as low as possible. The Weller MS (military standard) soldering tips with active tip technology are fully compliant with IPC industry standards (IPC - TM-650 2.5.33 Measurement of Electrical Overstress from Soldering Hand Tools) and are also MIL-SPEC compliant. Extend your Weller WX workbench with a micro soldering tool.

- Military Standard
- Very fine, slim soldering iron, ideal for working under the microscope
- High performance due to integrated active soldering tip
- Integrated direct suction: Retrofit kit T0052918599

- Active Tip Radiator Technology
- Heating time (approx) in seconds (50-350°C / 120-660°F): 3
- WX compatible

|                               |   |
|-------------------------------|---|
| item number                   | WL31202   |
| model                         | WXMP MS Set   |
| Specification                 | MIL-SPEC  |
| Technology                    | Active-Tip  |
| manufacturer                  | WELLER  |
| manufacturer item number      | T0052921799N  |
| GPSR manufacturer information | WELLER Tools GmbH<br>Carl-Benz-Strasse 2<br>DE-74354 Besigheim<br>www.weller.eu |
| order unit                    | 1 piece   |
| content unit                  | 1 piece   |
| product series                | Active Tip  |
| power                         | 40 W  |
| voltage                       | 12 V  |
| warm-up period                | 3 s   |
| handle type                   | soldering iron  |
| temperature range °C          | 100 – 450 °C  |
| temperature range °F          | 200 – 850 °F  |
| suitable tips                 | RTM MS / RTP MS   |
| Tip series                    | RTM-MS, RTP-MS  |
| included stand                | WDH 51  |
| included soldering tip        | RTM 013 S MS (RT 3MS)   |
| included soldering iron       | WXMP MS   |
| suitable control unit         | WX 1, WX 2, WXA 2, WXD 2, WXR 3   |
| ESD safe                      | yes   |