

## ESD Soldering gun for modular stations, AP250-B



This tool is ideal for repetitive tasks and, with its improved ergonomic design, ensures maximum comfort when working.

AP250-B ensures easy control and administration of the amount of tin dispensed pushing the trigger with one hand. Additionally, it incorporates an anti-rotation screw which adjusts cartridge alignment to suit the component.

|                          |         |
|--------------------------|---------|
| item number              | WL32736 |
| model                    | AP250-B |
| manufacturer             | JBC     |
| manufacturer item number | AP250-B |
| length with packaging    | 245 mm  |

|                              |  |
|------------------------------|--|
| width with packaging         | 185 mm   |
| height with packaging        | 45 mm  |
| scope of supply              | soldering pistol<br>Soldering tip: C250403<br>Tin coil: SN5450 |
| order unit                   | 1 piece  |
| content unit                 | 1 piece  |
| nominal power                | 50 W   |
| voltage                      | 24 V   |
| handle type                  | soldering gun  |
| with soldering tip           | yes  |
| compatible soldering station | CA   |
| suitable stand               | AP-SD  |
| suitable tips                | C250   |
| soldering tip shape          | other  |
| soldering tip diameter       | 1 mm   |
| included soldering tip       | C250403  |
| suitable accessories         | F1204 Fume extractor   |
| suitable control unit        | DI, DDE, DME   |
| ESD safe                     | yes  |
| wire diameter                | 0.06 – 1.5 mm  |