KAPTON ESD solder masking tape, 6 mm / 33 m



- High-temperature polyamide film with silicone adhesive
- brown-transparent
- ESD-compliant
- Thickness: 65 µm
- Adhesion to steel: 650 g/f/in (ASTM D3330)
- Tensile strength: 5 kg/f/c (ASTM D3759)
- Elongation: 63 % (ASTM D3759)
- Insulation class: 200 UL file E203272
- Chemical resistance: Good (test at 180°C/hour in a heating cabinet)
- Static charges: < 50 volts (@ 50% RH, 20°C) in use!
- Operating temperature: -73□~260□ x10min (ATSM D149)
- Shelf life: Maximum 1 year when stored in a cool and dry place < 24°C
- Operating temperature: 10^9 (CCT method)
- Purity: ISO 6 compliant
- Rolls: Core 76 mm - Length 33 m

Item no.	**WL32742**
Model	42-020-0006
Manufacturer	WEIDINGER

GPSR manufacturer data	Weidinger GmbH Hertha-Sponer-Str. 1a DE-82216 Gernlinden www.weidinger.eu
Length	33000 mm
Width	6 mm
Sales unit	1 rolls
Content unit	1 rolls
Material	polyimide
ESD compliant	yes

Other versions

Item no.	Width
WL32742	**6 mm**
WL32743	9 mm
WL32748	12.7 mm
WL32749	16 mm
WL32751	25 mm