

WR 2000ER, digital 2-channel rework station, 250 W (300 W)



Rework on highest level

One station meets the requirements of a rework workplace. Unique connecting compatibility of all tools. 2 independent tool channels with automatic tool recognition guarantee the simultaneous operation of 2 soldering tools. Tools are permanently ready for use.

The Weller Rework station WR 2 is a versatile soldering and desoldering station for professional repair work on electronic components of the latest technology in industrial production technology as well as in the repair and laboratory sector. The WR 2 has two independent tool-specific channels with automatic tool recognition and activation. Simultaneous soldering and desoldering or soldering and hot air soldering is thus possible at any time. With the exception of the Weller High-Speed Tools, all soldering tools such as soldering irons, solder baths, desoldering irons or hot air irons can be operated with the rework station.

- Repair kit for soldering and desoldering
- Overcurrent release: 1.6 A
- WT compatible
- incl. PDN desoldering pliers for changing suction nozzles

Item no.	WL33470
Model	WR 2000 ER
Model line	WR 2
Manufacturer	WELLER
Manufacturer article no.	T0053380870N
GPSR manufacturer data	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller.eu
Length	273 mm
Width	235 mm
Height	102 mm
Scope of delivery	1x WR 2 supply unit 1x WP 65 soldering iron 1x desoldering iron DSX 120 1x safety shelf WDH 10 1x safety shelf WDH 30 1x desoldering nozzle pliers PDN 1x desoldering nozzle XDS 1 1x soldering tip XNT A 1x mains plug 1x operating instructions
Length in inches	10.75 in
Width in inches	9.2 in
Height in inches	4.02 in
Sales unit	1 piece
Content unit	1 piece
Power	250 W
Rated power	300 W
Voltage	230 V
Temperature range °C	50 – 550 °C
Temperature range °F	150 – 950 °F
Temperature accuracy °F	±17 °F
Station (type)	soldering station
Included storage	WDH 30, WDH 10
Included soldering tip	XNT A
Included control unit	WR 2
Included desoldering iron	DSX 120
Included soldering iron	WP 65

Included suction nozzles	XDS 1
Included tool	PDN
Temperature stability °C	±2 °C
Temperature stability °F	±4 °F
ESD compliant	no

