

ESD Precision Electronic Gripper, flat round



Precision Electronics Gripping Pliers ESD The range for the highest demands on performance and results. Precision pliers for fine assembly work, e.g. in electronics and precision mechanics. For gripping, holding and bending. Handles electrically conductive - dissipative. Bolted joint: precise, backlash-free movement of the pliers. Precisely machined joint surfaces for smooth, low-friction movement throughout the entire opening range. Low-friction double spring for smooth and even opening. Smoothly ground gripping surfaces; edges carefully deburred. Non-glare finish. Light weight. Ergonomic, two-tone, multi-component ESD handles; black/gray. flat-round jaws. - Shape: 2 - Jaw length (B): 22.7mm - Jaw thickness (at joint) (D): 6.5mm - Tip width (E): 1.6mm - Tip thickness (F): 1.6mm - Head width (A): 11.2mm - ESD: Yes

- The range for the highest demands on performance and results
- Precision pliers for fine assembly work, e.g. in electronics and precision mechanics
- For gripping, holding and bending
- Handles electrically conductive dissipative
- Bolted joint: precise, backlash-free operation of the pliers
- Precisely machined joint surfaces for smooth, low-friction movement over the entire opening range
- Low-friction double spring for smooth and even opening
- Smoothly ground gripping surfaces
- Edges carefully deburred
- Glare-free finish
- Low weight
- Ergonomic, two-colour multi-component ESD handles
- Black/grey

item number WL33521







Products for the electronic industry







model	34 22 130 ESD
manufacturer	KNIPEX
manufacturer item number	34 22 130 ESD
length	125 mm
width	60 mm
height	18 mm
length with packaging	189 mm
width with packaging	72 mm
height with packaging	48 mm
Packaging volume	0.637 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	single pack
standards	DIN EN 61 340-5, DIN ISO 9655
RoHS conform	no
surface	burnished
VDE	no
ESD safe	yes
type of handle	with multi-component handles
type of pliers	electronic pliers







