

PreciForce® crimping pliers, black oxide finish, for insulated + uninsulated wire end ferrules, 220 mm



KNIPEX PreciForce® Consistently high crimp quality due to precision inserts and positive lock (unlockable). Crimping pressure is precisely set (calibrated) at the factory, adjustable. Force amplification through knee lever for low-fatigue work. Good handling due to favourable handle position, low weight, short design and ergonomically shaped handles. - Application: insulated + uninsulated wire-end ferrules - Capacity square millimetres: 0.25 - 6.0mm² - Number of nests: 5 - AWG: 23 - 10

- Consistently high crimp quality due to precision inserts and positive lock (can be unlocked)
- Crimp pressure is precisely set (calibrated) at the factory, adjustable
- Force amplification through knee lever for fatigue-free work
- Good handling due to favourable handle position, low weight, short design and ergonomically shaped handles

Item no.	WL33540
Model	97 52 38
Manufacturer	KNIPEX
Manufacturer article no.	97 52 38
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	230 mm
Width	58 mm

Products for the electronic industry



Height	21 mm
Length with packaging	225 mm
Width with packaging	75 mm
Height with packaging	30 mm
Volume with packaging	0.506 dm ³
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Incl. battery	no
Product series	PreciForce®
RoHS compliant	no
Surface	burnished
VDE	no
Crimping application	insulated + uninsulated ferrules
Number of crimp nests	5
ESD compliant	no
AWG	23 - 10
Crimp profile	Trapezoidal crimp
Tool length	220 mm
Grip (expression)	with multi-component sleeves
Type of pliers	automatic crimping tool