

Self-adjusting crimping pliers for end sleeves (ferrules) with front entry, black oxide finish, 190 mm



Crimping pliers for wire end ferrules For crimping wire end ferrules according to DIN 46228 part 1 + 4. Self-adjusting adjustment to the required wire end ferrule size: no crimping errors due to using the wrong crimping insert. Frontal insertion of the wire-end ferrules into the tool. Consistently high crimp quality due to positive ratchet (can be unlocked). Crimp pressure is precisely set (calibrated) at the factory, adjustable. Force amplification by knee lever for fatigue-free working. High operating comfort due to handy design and low weight. Crimping from 0.08 to 10.0 mm² and 16.0 mm² in one profile. with selection lever for setting the crimping range 0.08 to 10 or 16.0 mm². especially suitable for all twin wire-end ferrules up to 2 x 6 mm² or 2 x AWG 8. - Application: Wire end ferrules - Capacity square millimetres: 0.08 - 10 / 16mm² - Number of nests: 1 - AWG: 28 - 5.

- For crimping ferrules according to DIN 46228 part 1 + 4
- Self-adjusting adjustment to the required wire end ferrule size: no crimping errors due to use of the wrong crimp insert
- Frontal insertion of the wire-end ferrules into the tool
- Consistently high crimp quality due to positive ratchet (can be unlocked)
- Crimp pressure is precisely set (calibrated) at the factory, adjustable
- Force amplification through toggle lever for low-fatigue work
- High operating comfort due to handy design and low weight

item number **WL33541**

model **97 53 09**

Products for the electronic industry



manufacturer	KNIPEX
manufacturer item number	97 53 09
GPSR manufacturer information	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
length	190 mm
width	20 mm
height	23 mm
length with packaging	190 mm
width with packaging	20 mm
height with packaging	23 mm
Packaging volume	0.087 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	single pack
RoHS conform	no
surface	burnished
VDE	no
application crimp	Wire end ferrules
Number of crimp nests	1
crimp profile	Square crimp automatic
tool length	190 mm
AWG	28 - 5
type of handle	with multi-component sleeves
type of pliers	automatic crimping tool