

SONOREX DIGIPLUS ultrasonic bath, 9.7 litres



- oscillating tank inner dimensions (L x W x D): 300 x 240 x 150 mm
- Heating power: 400 Watt
- External dimensions (L x W x D): 325 x 265 x 305 mm
- Power adjustment from 20 to 100 % in 10 % steps
- Cleaning of sensitive materials
- Mixing of samples
- Homogenization of samples for analysis
- Rapid degassing of solvents for HPLC
- Performance features:
 - Power setting 20 to 100
 - Heating from 20 to 80 °C, thermostatically adjustable, LED display
 - Warning LED for overtemperature
 - Automatic short-time ultrasonic addition during heating to avoid boiling delay, can be switched off
 - Timer with minute preselection or continuous operation

- DEGAS - rapid degassing function
- SweepTec® - continuous sonic field oscillation for even and gentle cleaning
- Automatic safety switch-off 12 hours after last keystroke
- Filling level marking for safe dosing
- Drain cock for easy emptying, one-piece welded outlet bend
- Increased spray water protection IP 33 due to permanently connected mains cable and liquid-tight housing front.

item number	WL34058
model	DL 510 H
manufacturer	BANDELIN
manufacturer item number	7183
length	325 mm
width	265 mm
height	300 mm
order unit	1 piece
content unit	1 piece
content in liter	9.7 l
nominal power	140 W
max. ultrasonic power	580 W