Extraction cabinet CBC-A with 160 mm connection for central extraction, 180 to 230 m^3/h



• 80 % lower energy costs compared to a conventional extraction hood. The CBC-A requires only 200 m^3/h, conventional hoods 1000 m^3/h extraction volume.
• Mobile use on a work table or trolley.
• Large front opening enables a large working area that is not obstructed by a glass panel.
• Low noise level
• Cabinet interior: Fluorescent tube lighting (2 x 39 W). 4 pcs. 230 volt appliance connection sockets
• The CBC-A extraction cabinet with air barrier has a unique ventilation concept that separates the user from the application by means of a double air barrier, with unrestricted access to the workbench. The cabinet is located directly on the workbench and can be connected to a central extraction system via the 160 mm connection. Required minimum extraction volume: 180 m^3/h. Maximum extraction volume: 230 m^3/h.
• Also available as 120 V version: CBCA112G02G65I2115

Item no.	**WL34175**

Model	CBCA112G02G65I2
Manufacturer	WELLER
Manufacturer article no.	CBCA112G02G65I2N
GPSR manufacturer data	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller-tools.com
Length	760 mm
Width	1275 mm
Height	625 mm
Sales unit	1 piece
Content unit	1 piece
Frequency	50 Hz
Power	65 W
Voltage	230 V
Sound level	49 dBA
ESD compliant	yes