

ESD push handle trolley, 1 shelf, 500 kg, 850 x 500 mm



- Electrically conductive design
- Welded steel tube and profile steel
- electrically conductive powder-coated
- slate grey RAL 7015
- Screw and plug-in construction
- 1 Floor made of electrically conductive wood-based panel according to DIN 68765 in light grey
- 2 swivel castors and 2 fixed castors
- Wheels with TPE-ESD tyres (thermoplastic elastomer)
- electrically conductive
- Hubs with precision deep groove ball bearings
- Very low starting, rolling and swivel resistance
- · Quiet running on level floors
- Tyres not chalking (non-marking)
- Castor brakes, according to the European standard EN 1757-3







Products for the electronic industry





29.03.2024



item number	WL34205
model	ESD-Premium-Schiebebügelwagen
manufacturer	FETRA
manufacturer item number	9500
length	970 mm
width	509 mm
height	950 mm
order unit	1 piece
content unit	1 piece
colour manufacturer	slate grey
Colour	grey
material	wood-based panel
material frame	sectional steel
self-weight	24 kg
model transport trolley	handlebar cart
load capacity	500 kg
number of fixed castors	2
number of swivel castors	2
tyres	TPE ESD
tyre diameter	160 mm
wheel bearing	ball bearing
load platform length	850 mm
load platform width	500 mm
load heigth	235 mm
ESD safe	yes









2/2