

ESD handle roller, 2 platforms, 250 kg, 600 x 450 mm

The ESD handle roller of Fetra can be easily moved with the one-hand operation for the fast small transport up to 250 kg.

- Electrically conductive design
- Welded steel tube and profile steel
- electrically conductive powder-coated
- slate grey RAL 7015
- Screw and plug-in construction
- Shelves made of electrically conductive wood-based panel according to DIN 68765 in light grey
- 2 swivel castors and 2 fixed castors
- Wheels with TPE-ESD tyres (thermoplastic elastomer)
- electrically conductive
- Hubs with precision deep groove ball bearings
- Very low starting, rolling and swivel resistance
- Quiet running on level floors
- Tyres not chalking (non-marking)
- Castor brakes, according to the European standard EN 1757-3

item number	WL34213
manufacturer	FETRA
manufacturer item number	1820
GPSR manufacturer information	fetra Fechtel Transportgeräte GmbH Industriestraße 17-21 DE-33829 Bogenhausen www.fetra.de
length	860 mm
width	450 mm
height	910 mm
order unit	1 piece
content unit	1 piece
colour manufacturer	slate grey
Colour	grey
material	wood-based panel
material frame	sectional steel

self-weight	15 kg
model transport trolley	dolly
load capacity	250 kg
number of fixed castors	2
number of swivel castors	2
tyres	TPE ESD
tyre diameter	125 mm
wheel bearing	ball bearing
load platform length	600 mm
load platform width	450 mm
number of shelves	2
shelf height 1	195 mm
shelf height 2	770 mm
ESD safe	yes